



TECHNICAL DATA SHEET

DESIMA

Weiherrstrasse 3
D-88682 Salem

PRODUCT: **DESIMA POWER GLUE**

DESCRIPTION: An adhesive based on modified starch, dispersion of vinyl-maleine-acrylic copolymer

Technical Data

Physical State:	Thick paste
Form/colour:	Off white
Odour:	Mild
Solubility in Water	Miscible
Solubility in Organics	Immiscible
Viscosity @ 20°C (mPas)	20000 - 25000
Specific Gravity	1,09+/-0,05 g/cm ³
pH	5.5 – 6.5

APPLICATION: For hanging glass fibre wallpapers, textile wallpapers and blown wallpapers.

SURFACE PREPARATION: Surface should be dry, free of grease and other impurities; surfaces painted with glossy paints should be sandpapered; new and absorbent surfaces should be primed.

USAGE INSTRUCTIONS: After opening the container, the adhesive contents should be stirred well; apply the adhesive directly on the surface using a paint roller or paintbrush; excess of the adhesive should be removed with a cloth or sponge.

EFFICIENCY: 1kg of adhesive for 5-6 m²

PACKING: Plastic tightly closed buckets of capacity:
10,0 kg

<u>STORAGE:</u>	Prevent from freezing.
<u>EXPIRY DATE:</u>	12 months from the delivery date.
<u>FIRST AID:</u>	
<u>INHALATION:</u>	In normal conditions the product is not hazardous.
<u>SKIN CONTACT:</u>	After work wash hands with warm water.
<u>EYE CONTACT:</u>	Wash eyes with clean water; get medical attention if any discomfort continues.
<u>INGESTION:</u>	Rinse mouth with plenty of water; get medical attention if any discomfort continues.
<u>FIRE:</u>	Non flammable

*Information given in this sheet is based on our current knowledge and experience.
The product should be used in accordance with the currently valid regulations and good occupational hygiene practice. The presented information does not apply to mixtures of the product with other substances.
Use of the above given data, as well as the use of the product itself lie beyond the producer's control, thus setting rules of safe usage is the obligation of the user.*